

SEPR-Report EN 13215:2016 E

Model: B8-KSJ-10X

Refrigerant: R404A Arith. Mean Temp.

S.I.

Item	Symbol	Value (LT)	Unit
Evaporating Temperature	t	-35	°C
<b>Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K</b>			
Rated Cooling Capacity	Q <sub>A</sub>	1.07	kW
Rated Power Input	P <sub>A</sub>	1.03	kW
Rated COP	COP <sub>A</sub>	1.04	
<b>Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K</b>			
Cooling Capacity	Q <sub>2</sub>	1.23	kW
Power Input	P <sub>2</sub>	1.02	kW
COP	COP <sub>2</sub>	1.21	
<b>Parameters at full load and ambient temperature 43 °C, Subcooling 0.0 K</b>			
Cooling Capacity	Q <sub>3</sub>	0.80	kW
Power Input	P <sub>3</sub>	1.01	kW
COP	COP <sub>3</sub>	0.79	
<b>Other Items</b>			
Capacity Control		Fixed	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: climate.emerson.com/en-gb		