

## SEPR-Report EN 13215:2016 E

Model: P8-LL-40X

Refrigerant: R404A Arith. Mean Temp.

S.I.

Item	Symbol	Value (MT)	Unit
Evaporating Temperature	t	-10	°C
Annual Electricity Consumption	E	19762	kWh/a
Seasonal Energy Performance Ratio	SEPR	2.85	
<b>Parameters at full load and ambient temperature 32 °C, Subcooling 0.0 K</b>			
Rated Cooling Capacity	$Q_A$	9.17	kW
Rated Power Input	$P_A$	4.50	kW
Rated COP	$COP_A$	2.04	
<b>Parameters at full load and ambient temperature 25 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	$Q_B$	10.32	kW
Declared Power Input	$P_B$	4.23	kW
Declared COP	$COP_B$	2.44	
<b>Parameters at full load and ambient temperature 15 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	$Q_C$	11.96	kW
Declared Power Input	$P_C$	3.84	kW
Declared COP	$COP_C$	3.12	
<b>Parameters at full load and ambient temperature 5 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	$Q_D$	13.60	kW
Declared Power Input	$P_D$	3.55	kW
Declared COP	$COP_D$	3.83	
<b>Parameters at full load and ambient temperature 43 °C, Subcooling 0.0 K</b>			
Declared Cooling Capacity	$Q_3$	7.36	kW
Declared Power Input	$P_3$	4.84	kW
Declared COP	$COP_3$	1.52	
<b>Other Items</b>			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: <a href="http://climate.emerson.com/en-gb">climate.emerson.com/en-gb</a>		