

SEPR-Report EN 13215:2016 E

Model: ZXLE030E-PFJ

Refrigerant: R407A Arith. Mean Temp.

S.I.

Item	Symbol	Value (LT)	Unit
Evaporating Temperature	t	-35	°C
Annual Electricity Consumption	E	8719	kWh/a
Seasonal Energy Performance Ratio	SEPR	1.93	
Parameters at full load and ambient temperature 32 °C, Subcooling 30.6 K			
Rated Cooling Capacity	Q_A	2.26	kW
Rated Power Input	P_A	1.88	kW
Rated COP	COP_A	1.20	
Parameters at full load and ambient temperature 25 °C, Subcooling 27.2 K			
Declared Cooling Capacity	Q_B	2.42	kW
Declared Power Input	P_B	1.57	kW
Declared COP	COP_B	1.54	
Parameters at full load and ambient temperature 15 °C, Subcooling 21.4 K			
Declared Cooling Capacity	Q_C	2.59	kW
Declared Power Input	P_C	1.26	kW
Declared COP	COP_C	2.05	
Parameters at full load and ambient temperature 8 °C, Subcooling 16.6 K			
Declared Cooling Capacity	Q_D	2.66	kW
Declared Power Input	P_D	1.13	kW
Declared COP	COP_D	2.36	
Other Items			
Capacity Control		Fixed	
Degradation Coefficient	Cds	0.25	
Unit suction line temperature	t11	20.00	°C
Contact Details	Emerson Commercial & Residential Solutions - European Headquarters - Pascalstrasse 65 - 52076 Aachen, Germany Phone: +49 (0) 2408 929 0 - Fax: +49 (0) 2408 929 570 - Internet: climate.emerson.com/en-gb		